



VIBRASOUND® – Feel the sound !.

Convert your restaurant walls, ceilings, dining table, windows, bar tops etc. into intimate, non intrusive, high quality sounding boards. These incredible Vibrasound transducers transform any amplified audio output signal (no greater than 20 watts RMS recommended) into a manageable discrete sound source.

Simply attach the device to almost any existing surface i.e Wooden panels, Glass windows, Perspex sheets, Plasterboard - sit back and listen to the amazing results. Why not convert your conservatory or greenhouse into your garden sound system?

No unsightly speaker cabinets or ceiling speaker grills, no holes in walls or ceilings, Vibrasound is truly invisible.

Vibrasound transducers work through an energising principle, sending frequency waves across both sides of the activated surface producing a non directional, diffuse sound that fills the whole of the immediate area with “even” sound.



Spectacular result !



➤ Your stores communicate from the inside to the outside through your windows !.

➤ No more “deaf” plasma and lcd screens inside your store.

Travel or real estate agencies, but also AV stores will be able to communicate with video and audio for the people located in front of the shop window.

➤ **bars, cafés and restaurants** can now expand their ambiance to the outside and attract further people, even before they enter the site.

➤ Think of your **displays**, restaurant **tables** and **furniture**

becoming discrete speakers as well. .

➤ **Vandalproof** : you'll play music through your window knowing that no one is going to break your Vibrasound which is safe inside you store.

Specifications :

Power Handling & Freq. Response : 20 watts RMS continuous music.

20Hz - 20KHz dependent on size & thickness of energised surface.

8 ohm nominal impedance.

Dimensions : 120 mm x 46.0mm - Weight 1 kilo

Construction : 1 Inch edge wound aluminium voice coil with Ferro fluid to aid heat dissipation.

Alcino ferrite magnet. 5/16 Inch female threaded insert to accommodate mounting foot.

Fully sealed lexan plastic casing, waterproof, corrosion resistant.

